




MSA	Depth	Kg
04.311-075	75 mm	0.140

Rigid steel fixed saw frame with plastic handle.



MSA	Depth	Kg
04.316-075	75 mm	0.175
04.316-100	100 mm	0.185


Rigid stainless steel adjustable saw frame with plastic handle. Steel tension screw to tighten the saw blades.



MSA	Depth	Kg
04.315-060	60 mm	0.150
04.315-070	70 mm	0.150
04.315-080	80 mm	0.153
04.315-100	100 mm	0.170
04.315-120	120 mm	0.180
04.315-150	150 mm	0.190
04.315-200	200 mm	0.210

Saw frame made of rigid and resistant steel, with black varnished wooden handle

Delivered with 1 toothed plate and fixing screws to firmly hold the saw blades in place. Tension screw to tighten the saw blades.



MSA	Depth	Kg
04.310-060	60 mm	0.140
04.310-070	70 mm	0.145
04.310-080	80 mm	0.150
04.310-100	100 mm	0.155
04.310-120	120 mm	0.165
04.310-150	150 mm	0.174
04.310-200	200 mm	0.194

Saw frame made of rigid and resistant steel, with black varnished wooden handle.

Delivered with 1 toothed plate and fixing screws to firmly hold the saw blades in place.

## Spare parts for MSA04.310-x and MSA04.315-x:

MSA	Item	Kg
04.310-A	(1) Saw blades screw	0.007
04.310-B	(2) Upper screw	0.005
04.310-C	(3) Fixing plate for saw blades	0.002
04.310-D	(4) Washer for saw blades	0.001