

Ø 1.00 mm



Goupille fendue ; acier inoxydable.

Open-end pin ; stainless steel.

Splint ; Edelstahl.

Grupilla hendida ; acero inoxidable.

Copiglia spaccata ; acciaio inossidabile.

Cavilha rachada ; aço inoxidável.

100  
pcs

MSA	Longueur/Length mm	Kg
46.281-04	4	0.004
46.281-06	6	0.006
46.281-08	8	0.007
46.281-10	10	0.010
46.281-12	12	0.011
46.281-14	14	0.013
46.281-15	15	0.014
46.281-16	16	0.015
46.281-17	17	0.015
46.281-18	18	0.017
46.281-19	19	0.017
46.281-20	20	0.018
46.281-21	21	0.019
46.281-22	22	0.020
46.281-23	23	0.020
46.281-24	24	0.021
46.281-25	25	0.022
46.281-26	26	0.024
46.281-27	27	0.024
46.281-28	28	0.025
46.281-29	29	0.026
46.281-30	30	0.027

10  
pcs

MSA	Longueur/Length mm	Kg
46.291-04	4	0.001
46.291-06	6	0.001
46.291-08	8	0.001
46.291-10	10	0.001
46.291-12	12	0.001
46.291-14	14	0.001
46.291-15	15	0.001
46.291-16	16	0.002
46.291-17	17	0.002
46.291-18	18	0.002
46.291-19	19	0.002
46.291-20	20	0.002
46.291-21	21	0.002
46.291-22	22	0.002
46.291-23	23	0.002
46.291-24	24	0.002
46.291-25	25	0.002
46.291-26	26	0.003
46.291-27	27	0.003
46.291-28	28	0.003
46.291-29	29	0.003
46.291-30	30	0.003