(in accordance with Regulation (EU) 2015/830)



1T01060-AGUA DE TOQUE 24K PT

Version 1 Date of compilation: 26/06/2015

Page 1 of 10 Print date: 01/06/2021 **Version 7 (replaces version 6)** Revision date: 06/05/2021

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name:

AGUA DE TOQUE 24K PT

Product Code: 1T01060

1.2 Relevant identified uses of the substance or mixture and uses advised against.

USO INDUSTRIAL

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company:

TECHNOFLUX, S.L.

Address:

CTRA. GRANOLLERS - LLIÇA D' AMUNT KM. 2,3

City:

08186 LLIÇA D' AMUNT

Province: Telephone: **BARCELONA** +34 938417277

E-mail:

tecnoflux@yahoo.es

1.4 Emergency telephone number: +34 938417277 Antonio Diaz (Only available during office hours; Monday-Friday; 08:00-

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the substance or mixture.

In accordance with Regulation (EU) No 1272/2008:

Eye Dam. 1: Causes serious eye damage.

Ox. Liq. 3: May intensify fire; oxidiser.

Skin Corr. 1A: Causes severe skin burns and eye damage.

2.2 Label elements.

Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:





Signal Word:

Danger

H statements:

H272 May intensify fire; oxidiser.

H314 Causes severe skin burns and eye damage.

P statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash ... thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor/...

P370+P378 In case of fire: Use... to extinguish.

(in accordance with Regulation (EU) 2015/830)



1T01060-AGUA DE TOQUE 24K PT

Version 1 Date of compilation: 26/06/2015

Page 2 of 10 Print date: 01/06/2021 Version 7 (replaces version 6) Revision date: 06/05/2021

Contains: nitric acid hydrogen chloride

2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not Applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

			(*)Classification - Regulation (EC) No 1272/2008	
Identifiers	Name	Concentrate	Classification	specific concentration limit
Index No: 007-004- 00-1 CAS No: 7697-37-2 EC No: 231-714-2 Registration No: 01- 2119487297-23-XXXX	[1] nitric acid	72%	Ox. Liq. 3, H272 - Skin Corr. 1A, H314	Skin Corr. 1A, H314: $C \ge 20$ % Skin Corr. 1B, H314: 5 % $\le C$ < 20 % Ox. Liq. 3, H272: $C \ge 65$ %
Index No: 017-002- 00-2 CAS No: 7647-01-0 EC No: 231-595-7 Registration No: 01- 2119484862-27-XXXX	[1] hydrogen chloride	8%	Acute Tox. 3, H331 - Skin Corr. 1A, H314	-

^(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration.

Eye contact.

Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Dont let the person to rub the affected eye.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners. The use of personal protective equipment is recommended for people providing first aid (see section 8).

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Corrosive Product, contact with eyes or skin can cause burns; ingestion or inhalation can cause internal damage, if this occurs immediate medical assistance is required.

^[1] Substance with a Community workplace exposure limit (see section 8.1).

(in accordance with Regulation (EU) 2015/830)



1T01060-AGUA DE TOQUE 24K PT

Version 1 Date of compilation: 26/06/2015

Page 3 of 10 Print date: 01/06/2021 Version 7 (replaces version 6) Revision date: 06/05/2021

Contact with eyes may cause irreversible damage.

4.3 Indication of any immediate medical attention and special treatment needed.

Request immediate medical attention. Never administer anything orally to persons who are unconscious. Do not induce vomiting. If the person vomits, clear the respiratory tract. Cover the affected area with a dry sterile bandage. Protect the affected area from pressure or friction.

SECTION 5: FIREFIGHTING MEASURES.

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the substance or mixture.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

(in accordance with Regulation (EU) 2015/830)



1T01060-AGUA DE TOQUE 24K PT

Date of compilation: 26/06/2015 Version 1

Page 4 of 10 Print date: 01/06/2021 **Version 7 (replaces version 6)** Revision date: 06/05/2021

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

Classification and threshold amount of storage in accordance with Annex I to Directive 2012/18/EU (SEVESO III):

		Qualifying quantity (tonnes) for the application of	
Code	Description	Lower-tier requirements	Upper-tier requirements
P8	OXIDISING LIQUIDS AND SOLIDS	50	200

7.3 Specific end use(s).

Not available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m³
	7697-37-2	European	Eight hours		
		Union [1]	Short term	1	2,6
		United	Eight hours		
		Kingdom [2]	Short term	1	2,6
		Éire [3]	Eight hours		
nitric acid			Short term	1	2,6
Thate dela		United States	Eight hours	2	
		[4] (Cal/OSHA)	Short term	4	
		United States	Eight hours	2	
		[5] (NIOSH)	Short term	4	
		United States	Eight hours	2	5
		[6] (OSHA)	Short term		
	7647-01-0	European	Eight hours	5	8
		Union [1]	Short term	10	15
		United	Eight hours	1	2
		Kingdom [2]	Short term	5	8
		Éire [3]	Eight hours	5	8
hydrogen chloride			Short term	10	15
Trydrogen emonde		United States	Eight hours	0.3	(Ceiling) 2
		[4] (Cal/OSHA)	Short term		
		United States	Eight hours	(Ceiling) 5	
		[5] (NIOSH)	Short term		
		United States	Eight hours	(Ceiling) 5	(Ceiling) 7
547.A		[6] (OSHA)	Short term	15	(705(1))

^[1] According both Binding Occupational Esposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value

^[2] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adobted by Health and Safety Executive.

^[3] According Code of Practice for the Safety, Health and Welfare at Work (Chemicals Agents) Regulations adopted by Health and Safety Authority (HSA).

^[4] California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

^[5] National Institute for Occupational Safety and Health. NIOSH Recommendations for occupational safety and health, Compendium of Policy Documents and Statements, January, 1992, DHHS (NIOSH) Publication No. 92-100.

^[6] Occupational Safety and Health Administration, United States Department of Labor. Permissible Exposure limits (PELs), California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

(in accordance with Regulation (EU) 2015/830)



1T01060-AGUA DE TOQUE 24K PT

Date of compilation: 26/06/2015 Version 1

Page 5 of 10 Version 7 (replaces version 6) Revision date: 06/05/2021 Print date: 01/06/2021

hydrogen chloride CAS No: 7647-01-0 EC No: 231-595-7	DNEL (Workers)	Inhalation, Long-term, Local effects	8 (mg/m³)
--	-------------------	--------------------------------------	-----------

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %		
Uses:	USO INDUSTRIAL		
Breathing protect			
PPE:	Filter mask for protection against gases and particles.		
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.		
CEN standards:	EN 136, EN 140, EN 405		
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor. Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach		
Observations:	the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.		
Filter Type needed: Hand protection:	A2		
PPE:	Non-disposable protective gloves against chemicals.		
Characteristics:	«CE» marking, category III. Check the list of chemicals for which the glove has been tested.		
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420		
Maintenance:	A schedule for the periodical replacement of gloves should be established in order to guarantee their replacement before pollutants permeate them. The use of contaminated gloves could be more dangerous than not using gloves, since the pollutant can gradually accumulate in the glove's material.		
Observations:	They are to be replaced whenever tears, cracks or deformations are observed or when exterior dirt could reduce their strength.		
Material:	PVC (polyvinyl chloride) Breakthrough time (min.): Material thickness (mm): 0,35		
Eye protection:			
PPE: Characteristics:	Protective goggles with built-in frame. «CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.		
CEN standards:	EN 165, EN 166, EN 167, EN 168		
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.		
Observations:	Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.		
Skin protection:			
PPE:	Chemical protective clothing		
Characteristics:	«CE» marking, category III. Clothing should fit properly. The level of protection must be set according to a test parameter called BT (Breakthrough Time), which indicates how long it takes for the chemical to pass through the material.		
CEN standards:	EN 464,EN 340, EN 943-1, EN 943-2, EN ISO 6529, EN ISO 6530, EN 13034 In order to guarantee uniform protection, follow the washing and maintenance instructions provided by		
Maintenance:	the manufacturer. The protective clothing's design should facilitate correct positioning, staying in place without moving for		
Observations:	the period of use expected, bearing in mind environmental factors as well as any movement or position the user might adopt while carrying out the activity.		
PPE:	Anti-static safety footwear against chemicals.		
Characteristics:	«CE» marking, category III. Check the list of chemicals against which the footwear is resistant.		
CEN standards:	EN ISO 13287, EN 13832-1, EN 13832-2, EN 13832-3, EN ISO 20344, EN ISO 20345		

(in accordance with Regulation (EU) 2015/830)



1T01060-AGUA DE TOQUE 24K PT

Date of compilation: 26/06/2015 Version 1

Page 6 of 10 Print date: 01/06/2021 Version 7 (replaces version 6) Revision date: 06/05/2021

For correct maintenance of this kind of safety footwear, it is necessary to observe the instructions Maintenance:

specified by the manufacturer. The footwear should be replaced as soon as any sign of damage is

The footwear should be cleaned regularly and dried when damp, although it should not be placed too Observations:

close to a source of heat in order to avoid any sharp changes in temperature.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Appearance: Liquid with characteristic odour

Colour: N.A./N.A. Odour:acre sofocante Odour threshold: N.A./N.A.

pH:N.A./N.A.

Melting point: N.A./N.A. Boiling Point: N.A./N.A. Flash point: N.A./N.A. Evaporation rate: N.A./N.A.

Inflammability (solid, gas): N.A./N.A. Lower Explosive Limit: N.A./N.A. Upper Explosive Limit: N.A./N.A. Vapour pressure: N.A./N.A. Vapour density: N.A./N.A. Relative density: N.A./N.A. Solubility: N.A./N.A. Liposolubility: N.A./N.A. Hydrosolubility: N.A./N.A.

Partition coefficient (n-octanol/water): N.A./N.A.

Auto-ignition temperature: N.A./N.A. Decomposition temperature: N.A./N.A.

Viscosity: N.A./N.A.

Explosive properties: N.A./N.A. Oxidizing properties: N.A./N.A.

N.A./N.A. = Not Available/Not Applicable due to the nature of the product

9.2 Other information.

Dropping point: N.A./N.A.

Blink: N.A./N.A.

Kinematic viscosity: N.A./N.A.

N.A./N.A. = Not Available/Not Applicable due to the nature of the product

SECTION 10: STABILITY AND REACTIVITY.

If the storage conditions are satisfied, does not produce dangerous reactions.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

May intensify fire; oxidiser.

10.4 Conditions to avoid.

Avoid the following conditions:

- Contact with incompatible materials.

10.5 Incompatible materials.

Avoid the following materials:

- Flammable materials.
- Explosives materials.
- Toxic materials.
- Corrosive materials.

(in accordance with Regulation (EU) 2015/830)

Technoflux

1T01060-AGUA DE TOQUE 24K PT

Date of compilation: 26/06/2015 Version 1

Page 7 of 10 Print date: 01/06/2021 Version 7 (replaces version 6) Revision date: 06/05/2021

10.6 Hazardous decomposition products.

Depending on conditions of use, can be generated the following products:

- Oxygen.
- Oxidizing gases or vapors.

SECTION 11: TOXICOLOGICAL INFORMATION.

11.1 Information on toxicological effects.

There are no tested data available on the product.

Splatters in the eyes can cause irritation and reversible damage.

a) acute toxicity;

Not conclusive data for classification.

b) skin corrosion/irritation;

Product classified:

Skin Corrosive, Category 1A: Causes severe skin burns and eye damage.

c) serious eye damage/irritation;

Product classified:

Serious eye damage, Category 1: Causes serious eye damage.

d) respiratory or skin sensitisation;

Not conclusive data for classification.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Not conclusive data for classification.

h) STOT-single exposure;

Not conclusive data for classification.

i) STOT-repeated exposure;

Not conclusive data for classification.

i) aspiration hazard:

Not conclusive data for classification.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

No information is available regarding the ecotoxicity of the substances present.

12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.

No information is available on the degradability of the substances present. No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

No information is available regarding the bioaccumulation of the substances present.

12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

(in accordance with Regulation (EU) 2015/830)

Technoflux

1T01060-AGUA DE TOQUE 24K PT

Date of compilation: 26/06/2015 Version 1

Page 8 of 10 Print date: 01/06/2021 Version 7 (replaces version 6) Revision date: 06/05/2021

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

Land: Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

Sea: Transport by ship: IMDG. Transport documentation: Bill of lading Air: Transport by plane: ICAO/IATA. Transport document: Airway bill.

14.1 UN number.

UN No: UN2031

14.2 UN proper shipping name.

Description:

ADR: UN 2031, NITRIC ACID, 8 (5.1), PG I, (E) UN 2031, NITRIC ACID, 8 (5.1), PG I ICAO/IATA (Passenger aircraft): PROHIBITED

ICAO/IATA (Cargo aircraft): UN 2031, NITRIC ACID, 8 (5.1), PG I

14.3 Transport hazard class(es).

Class(es): 8

14.4 Packing group.

Packing group: I

14.5 Environmental hazards.

Marine pollutant: No

14.6 Special precautions for user.

Labels: 8, 5.1





Hazard number: 885 ADR LQ: 0 IMDG LQ: 0 ICAO LQ: Not applicable.

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR. Transport by ship, FEm - Emergency sheets (F - Fire, S - Spills): F-A,S-Q Proceed in accordance with point 6.

(in accordance with Regulation (EU) 2015/830)



1T01060-AGUA DE TOQUE 24K PT

Version 1 Date of compilation: 26/06/2015

Page 9 of 10 Print date: 01/06/2021 Version 7 (replaces version 6) Revision date: 06/05/2021

IMDG Code segregation group: 1 Acids

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

The product is not transported in bulk.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): P8

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

Classification codes:

Acute Tox. 3: Acute toxicity (Inhalation), Category 3 Eye Dam. 1 : Serious eye damage, Category 1 Ox. Liq. 3: Oxidising liquid, Category 3 Skin Corr. 1A: Skin Corrosive, Category 1A

Changes regarding to the previous version:

- Modification of the classification ADR/IMDG/ICAO/IATA/RID (SECTION 14).
- Addition of abbreviations and acronyms (SECTION 16).

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data Health hazards Calculation method Environmental hazards Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

European Agreement concerning the International Carriage of Dangerous Goods by Road. ADR:

European Committee for Standardization. CEN:

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be

considered a tolerable minimum.

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not

anticipated.

PPE: Personal protection equipment. IATA: International Air Transport Association. ICAO: International Civil Aviation Organization.

IMDG: International Maritime Code for Dangerous Goods.

Regulations Concerning the International Transport of Dangerous Goods by Rail. RID:

Key literature references and sources for data:

(in accordance with Regulation (EU) 2015/830)



1T01060-AGUA DE TOQUE 24K PT

Date of compilation: 26/06/2015 Version 1

Page 10 of 10 Revision date: 06/05/2021 Print date: 01/06/2021 **Version 7 (replaces version 6)**

http://eur-lex.europa.eu/homepage.html http://echa.europa.eu/

Regulation (EU) 2015/830 Regulation (EC) No 1907/2006. Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.