

Ø 1.20 mm



Goupille fendue ; acier inoxydable.

Open-end pin ; stainless steel.

Splint ; Edelstahl.

Grupilla hendida ; acero inoxidable.

Copiglia spaccata ; acciaio inossidabile.

Cavilha rachada ; aço inoxidável.

100  
pcs

MSA	Longueur/Length mm	Kg
46.282-04	4	0.004
46.282-06	6	0.006
46.282-08	8	0.007
46.282-10	10	0.010
46.282-12	12	0.011
46.282-14	14	0.013
46.282-15	15	0.014
46.282-16	16	0.015
46.282-17	17	0.015
46.282-18	18	0.017
46.282-19	19	0.017
46.282-20	20	0.018
46.282-21	21	0.019
46.282-22	22	0.020
46.282-23	23	0.020
46.282-24	24	0.021
46.282-25	25	0.022
46.282-26	26	0.024
46.282-27	27	0.024
46.282-28	28	0.025
46.282-29	29	0.026
46.282-30	30	0.027

10  
pcs

MSA	Longueur/Length mm	Kg
46.292-04	4	0.001
46.292-06	6	0.001
46.292-08	8	0.001
46.292-10	10	0.001
46.292-12	12	0.001
46.292-14	14	0.001
46.292-15	15	0.001
46.292-16	16	0.002
46.292-17	17	0.002
46.292-18	18	0.002
46.292-19	19	0.002
46.292-20	20	0.002
46.292-21	21	0.002
46.292-22	22	0.002
46.292-23	23	0.002
46.292-24	24	0.002
46.292-25	25	0.002
46.292-26	26	0.003
46.292-27	27	0.003
46.292-28	28	0.003
46.292-29	29	0.003
46.292-30	30	0.003