



Goupille fendue ; acier inoxydable.

Open-end pin ; stainless steel.

Splint ; Edelstahl.

Grupilla hendida ; acero inoxidable.

Copiglia spaccata ; acciaio inossidabile.

Cavilha rachada ; aço inoxidável.

**100**  
pcs

MSA	Longueur/Length mm	Kg
46.280-04	4	0.003
46.280-06	6	0.004
46.280-08	8	0.004
46.280-10	10	0.005
46.280-12	12	0.005
46.280-14	14	0.006
46.280-15	15	0.006
46.280-16	16	0.007
46.280-17	17	0.007
46.280-18	18	0.008
46.280-19	19	0.008
46.280-20	20	0.008
46.280-21	21	0.008
46.280-22	22	0.008
46.280-23	23	0.009
46.280-24	24	0.010
46.280-25	25	0.010
46.280-26	26	0.010
46.280-27	27	0.010
46.280-28	28	0.010
46.280-29	29	0.011
46.280-30	30	0.012

**10**  
pcs

MSA	Longueur/Length mm	Kg
46.290-04	4	0.001
46.290-06	6	0.001
46.290-08	8	0.001
46.290-10	10	0.001
46.290-12	12	0.001
46.290-14	14	0.001
46.290-15	15	0.001
46.290-16	16	0.001
46.290-17	17	0.001
46.290-18	18	0.001
46.290-19	19	0.001
46.290-20	20	0.002
46.290-21	21	0.002
46.290-22	22	0.002
46.290-23	23	0.002
46.290-24	24	0.002
46.290-25	25	0.002
46.290-26	26	0.002
46.290-27	27	0.002
46.290-28	28	0.002
46.290-29	29	0.002
46.290-30	30	0.002